



Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 02.01.2018

Page 1 of 12

Revision date: 10.26.2020

Plastopang

SECTION 1: Identification

Product identifier

Product name: Plastopang
Product code: 1090F/8 OZ, 1090F/QT, 1090F/GAL, 1090F/5GAL,
1090F/53GAL
Additional information: Rev 2

Recommended use of the product and restriction on use

Relevant identified uses: Not determined or not applicable.
Uses advised against: Not determined or not applicable.
Reasons why uses advised against: Not determined or not applicable.

Manufacturer or supplier details

Manufacturer:
North America
Tech International
200 East Coshocton Street
Johnstown, OH 43031
1-740-967-9015
www.tech-international.com

Supplier:
Australia
Chemvulc Industrial Australia Pty Ltd
Unit 3/11 Precision Place
Mulgrave, NSW 2756
+61 2 4587 9888
www.chemvulcind.com.au

Emergency telephone number:

United States
CHEMTREC
Within USA and Canada: 1-800-424-9300
Outside USA and Canada: +1-703-527-3887

Emergency telephone number:

Australia
Within Australia: 1-800-127406

SECTION 2: Hazard(s) identification

GHS classification:

Flammable liquids, category 2
Eye irritation, category 2A
Specific target organ toxicity - single exposure, category 3, central nervous system

Label elements

Hazard pictograms:



Signal word: Danger

Hazard statements:

H225 Highly flammable liquid and vapor.
H319 Causes serious eye irritation.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 02.01.2018

Page 2 of 12

Revision date: 10.26.2020

Plastopang

H336 May cause drowsiness or dizziness.

Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P271 Use only outdoors or in a well-ventilated area.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/light/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P264 Wash skin thoroughly after handling.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P370+P378 In case of fire: Use agents recommended in section 5 for extinction.

P303+P361+P353 If on skin (or hair): Immediately remove/take off all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists get medical advice/attention

P304+P340+P312 If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P405 Store locked up.

P403+P233 Store in a well ventilated place. Keep container tightly closed.

P403+P235 Store in a well ventilated place. Keep cool.

P501 Dispose of contents and container as instructed in Section 13.

Hazards not otherwise classified: None

SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS number: 67-64-1	Acetone	20-50
CAS number: 112945-52-5	Silica, amorphous, fumed, cryst.-free	1-5
CAS number: 78-93-3	Butanone	20-50

Additional Information:

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR §1910.1200).

SECTION 4: First aid measures

Description of first aid measures

General notes:

Show this Safety Data Sheet to the doctor in attendance

After inhalation:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 02.01.2018

Page 3 of 12

Revision date: 10.26.2020

Plastopang

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If experiencing respiratory symptoms, seek medical advice/attention

After skin contact:

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention

After eye contact:

Rinse eyes with plenty of gently flowing lukewarm water for 15 minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention

After swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention

Most important symptoms and effects, both acute and delayed

Acute symptoms and effects:

Eye contact may result in irritation, redness, pain, inflammation, itching, burning and tearing
Inhalation may have adverse effects on the central nervous system. Symptoms may include drowsiness, dizziness, headache, nausea and lowering of consciousness. Acute overexposure via inhalation may result in respiratory distress, confusion and unconsciousness
Product is highly flammable. Exposure to sources of ignition may cause physical injury

Delayed symptoms and effects:

Effects are dependent on exposure (dose, concentration, contact time)

Immediate medical attention and special treatment

Specific treatment:

Skin/eye burns require immediate treatment

Notes for the doctor:

Treat symptomatically

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media:

Dry chemical, CO₂, water spray or alcohol-resistant foam

Unsuitable extinguishing media:

Do not use water jet

Specific hazards during fire-fighting:

Highly flammable liquid. Will be easily ignitable by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard. Containers may explode when heated. Inhalation or contact with material may irritate or burn skin and eyes. Fire may produce irritating, corrosive and/or toxic gases. Vapors may cause dizziness or suffocation

Special protective equipment for firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA)

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 02.01.2018

Page 4 of 12

Revision date: 10.26.2020

Plastopang

with a full-face piece operated in positive pressure mode

Special precautions:

Evacuate non-essential personnel. Ventilate closed spaces before entering. Consider initial evacuation for 300 meters in all directions. If tank/rail car is involved in the fire, ISOLATE for 800 meters in all directions. Fight fire from a maximum distance. Move containers from fire area if you can do it without risk. Use water spray/fog for cooling fire exposed containers. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. Always stay away from tanks engulfed in fire. For massive fire, use unmanned hose holders or monitor nozzles. If this is impossible, withdraw from area and let fire burn. Stand by, at a safe distance, with extinguisher ready for possible re-ignition. A vapor-suppressing foam may be used to reduce vapors. Avoid unnecessary run-off of extinguishing media which may cause pollution. Do not handle damaged containers unless specialized to do so

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. All equipment used when handling the product must be grounded. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling

Environmental precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided

Methods and material for containment and cleaning up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. A vapor-suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers for future disposal. Dispose of in accordance with all applicable regulations (see Section 13)

Reference to other sections:

For personal protective equipment see Section 8. For disposal see Section 13

SECTION 7: Handling and storage

Precautions for safe handling:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating and lighting equipment. Take action to prevent static discharges. Handle containers with caution. Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Conditions for safe storage, including any incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

Occupational Exposure limit values:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 02.01.2018

Page 5 of 12

Revision date: 10.26.2020

Plastopang

Country (Legal Basis)	Substance	Identifier	Permissible concentration
ACGIH	Acetone	67-64-1	8-Hour TWA: 250 ppm
	Acetone	67-64-1	15-min STEL: 500 ppm
	Butanone	78-93-3	ACGIH TLV TWA: 200 ppm
	Butanone	78-93-3	ACGIH TLV STEL: 300 ppm
NIOSH	Acetone	67-64-1	REL (10-Hour workday): 590 mg/m ³ (250 ppm)
	Acetone	67-64-1	IDLH: 50 ppm
	Butanone	78-93-3	NIOSH IDLH 3,000 ppm
	Butanone	78-93-3	NIOSH STEL 300 ppm, 885 mg/m ³
	Butanone	78-93-3	NIOSH TWA 200 ppm, 590 mg/m ³
	Silica, amorphous, fumed, cryst.-free	112945-52-5	NIOSH REL TWA 6.0 mg/m ³
United States (OSHA)	Acetone	67-64-1	8-Hour TWA PEL: 2400 mg/m ³ (1000 ppm)
	Acetone	67-64-1	8-Hour TWA: 1800 mg/m ³ (750 ppm)
	Butanone	78-93-3	STEL: 300 ppm (885 mg/m ³)
	Butanone	78-93-3	OSHA PEL TWA 200 ppm, 590 mg/m ³
	Silica, amorphous, fumed, cryst.-free	112945-52-5	OSHA PEL TWA 20.0 Million particles per cubic foot
	Silica, amorphous, fumed, cryst.-free	112945-52-5	OSHA PEL TWA 0.8 mg/m ³ 80/(%SiO ₂)
United States (California)	Acetone	67-64-1	15-min STEL: 1780 mg/m ³ (750 ppm)
	Acetone	67-64-1	8-Hour TWA PEL: 1200 mg/m ³ (500 ppm)
	Acetone	67-64-1	Ceiling Limit: 3000 ppm

Biological limit values:

No biological exposure limits noted for the ingredient(s).

Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls.

Biological monitoring may also be appropriate for some substances.

Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above. Use explosion-proof ventilation equipment.

Personal protection equipment

Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

Skin and body protection:

Select glove material impermeable and resistant to the substance.

Wear appropriate clothing to prevent any possibility of skin contact.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 02.01.2018

Page 6 of 12

Revision date: 10.26.2020

Plastopang

For continuous contact we recommend nitrile gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified.

Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

Use a NIOSH/MSHA approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. Comply with the OSHA respirator regulations found in 29 CFR 1910.134.

General hygienic measures:

Avoid contact with skin, eyes and clothing.

Wash hands before breaks and at the end of work.

Wash contaminated clothing before reuse.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Viscous off-white colored liquid
Odor	Solvent Odor
Odor threshold	Not determined or not available.
pH	Not determined or not available.
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	>= 56°C (132.8°F)
Flash point (closed cup)	-9°C (15.8°F)
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Not determined or not available.
Upper flammability/explosive limit	13%
Lower flammability/explosive limit	1.8%
Vapor pressure	< 100 kPa at 23°C
Vapor density	Not determined or not available.
Density	0.84 g/cm ³
Relative density	Not determined or not available.
Solubilities	Not determined or not available.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	Not determined or not available.
Dynamic viscosity	3700 - 4500 mPa s @ 20°C
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

Other information

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 02.01.2018

Page 7 of 12

Revision date: 10.26.2020

Plastopang

SECTION 10: Stability and reactivity

Reactivity:

Not reactive under recommended handling and storage conditions.

Chemical stability:

Stable under recommended handling and storage conditions.

Possibility of hazardous reactions:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

Conditions to avoid:

Extreme heat, open flames, hot surfaces, sparks, ignition sources, static electricity and incompatible materials. Vapor accumulation in low or confined areas.

Incompatible materials:

None known.

Hazardous decomposition products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Acute toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Route	Result
Butanone	oral	LD50 - Mouse: 4050 mg/kg
	dermal	LD50 - Rabbit: 6480 mg/kg
	inhalation	LC50 - Rat: 23.5 mg/L (8 h)
Silica, amorphous, fumed, cryst.-free	oral	LD50 - Rat: 3160 mg/kg
Acetone	oral	LD50 - Rat: 5800 mg/kg
	inhalation	LC50 - Rat: 76 mg/L (4 h, vapor)
	dermal	LD50 - Rabbit: >7426 mg/kg

Skin corrosion/irritation

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

Name	Result
Silica, amorphous, fumed, cryst.-free	Causes skin irritation.

Serious eye damage/irritation

Assessment:

Causes serious eye irritation

Product data:

No data available.

Substance data:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 02.01.2018

Page 8 of 12

Revision date: 10.26.2020

Plastopang

Name	Result
Acetone	Causes serious eye irritation.
Butanone	Causes serious eye irritation.
Silica, amorphous, fumed, cryst.-free	Causes serious eye irritation.

Respiratory or skin sensitization

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

International Agency for Research on Cancer (IARC):

Name	Classification
Silica, amorphous, fumed, cryst.-free	Group 3 - Not classifiable as to its carcinogenicity to humans

National Toxicology Program (NTP): None of the ingredients are listed.

Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Reproductive toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Specific target organ toxicity (single exposure)

Assessment:

May cause drowsiness or dizziness

Product data:

No data available.

Substance data:

Name	Result
Butanone	May cause drowsiness or dizziness.
Silica, amorphous, fumed, cryst.-free	May cause respiratory irritation.
Acetone	May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 02.01.2018

Page 9 of 12

Revision date: 10.26.2020

Plastopang

Substance data: No data available.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Information on likely routes of exposure:

Oral, inhalation, dermal and ocular.

Symptoms related to the physical, chemical and toxicological characteristics:

See section 4 of this SDS.

Other information:

No data available.

SECTION 12: Ecological information

Acute (short-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Result
Acetone	LC50 - Oncorhynchus mykiss: 5540 mg/L (96 hours)

Chronic (long-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

Persistence and degradability

Product data: No data available.

Substance data:

Name	Result
Acetone	Readily biodegradable (90.9% degradation after 28 days).

Bioaccumulative potential

Product data: No data available.

Substance data:

Name	Result
Acetone	Very low potential for bioaccumulation (BCF: 3).

Mobility in soil

Product data: No data available.

Substance data: No data available.

Other adverse effects: No data available.

SECTION 13: Disposal considerations

Disposal methods:

Dispose in accordance with all applicable regulations. It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

SECTION 14: Transport information

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200


Initial preparation date: 02.01.2018

Page 10 of 12


Revision date: 10.26.2020

Plastopang


United States Transportation of dangerous goods (49 CFR DOT)

UN number	1133
UN proper shipping name	Adhesives, containing a flammable liquid
UN transport hazard class(es)	3 
Packing group	II
Environmental hazards	None
Special precautions for user	None
Passenger air/rail	5 L
Cargo aircraft only	60 L
Stowage category	B

International Maritime Dangerous Goods (IMDG)

UN number	1133
UN proper shipping name	Adhesives, containing flammable liquid
UN transport hazard class(es)	3 
Packing group	II
Environmental hazards	None
Special precautions for user	None
EMS number	F-E, S-D
Stowage category	B
Excepted quantities	E2
Limited quantity	5L

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	1133
UN proper shipping name	Adhesives, containing flammable liquid
UN transport hazard class(es)	3 
Packing group	II
Environmental hazards	None
Special precautions for user	None
ERG code	3L
Excepted quantities	E2
Passenger and cargo	5 L
Cargo aircraft only	60 L
Limited quantity	1 L

SECTION 15: Regulatory information

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 02.01.2018

Page 11 of 12

Revision date: 10.26.2020

Plastopang

United States regulations

Inventory listing (TSCA): All ingredients are listed or exempt.

Significant New Use Rule (TSCA Section 5): None of the ingredients are listed.

Export notification under TSCA Section 12(b): None of the ingredients are listed.

SARA Section 302 extremely hazardous substances: None of the ingredients are listed.

SARA Section 313 toxic chemicals: None of the ingredients are listed.

CERCLA:

67-64-1	Acetone	Listed	5000
78-93-3	Butanone	Listed	5000
67-64-1	Acetone	Listed	5000 lb

RCRA:

78-93-3	Butanone	Listed	U159
67-64-1	Acetone	Listed	U002

Section 112(r) of the Clean Air Act (CAA): None of the ingredients are listed.

Massachusetts Right to Know:

112945-52-5	Silica, amorphous, fumed, cryst.-free	Listed
78-93-3	Butanone	Listed
67-64-1	Acetone	Listed

New Jersey Right to Know:

112945-52-5	Silica, amorphous, fumed, cryst.-free	Not Listed
78-93-3	Butanone	Listed
67-64-1	Acetone	Listed

New York Right to Know:

112945-52-5	Silica, amorphous, fumed, cryst.-free	Not Listed
78-93-3	Butanone	Listed
67-64-1	Acetone	Listed

Pennsylvania Right to Know:

112945-52-5	Silica, amorphous, fumed, cryst.-free	Listed
78-93-3	Butanone	Listed
67-64-1	Acetone	Listed

California Proposition 65: None of the ingredients are listed.

SECTION 16: Other information

Abbreviations and Acronyms: None

Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

NFPA: 2-3-0

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 02.01.2018

Page 12 of 12

Revision date: 10.26.2020

Plastopang

HMIS: 2-3-0

Initial preparation date: 02.01.2018

Revision date: 10.26.2020

End of Safety Data Sheet